

**SPECIFICATIONS**

Item	Model		SUBARU TRAVIQ		
				S package	L package
			2WD 2.2L 4AT		
DIMENSIONS & WEIGHT	Overall length(mm)		4315		
	Overall width(mm)		1740		
	Overall height(mm)		1630(1675)*1	1630	1675
	Wheelbase(mm)		2695		
	Tread(mm)	Front	1470	1460	1470
		Rear	1485	1475	1485
	Minimum ground clearance at CW(mm)		150		
Curb weight(kg)		1460(1470)*1	1470(1480)*2	1480	
ENGINE	Type		Inline 4-Cylinder,4-Stroke,gasoline,16-valve		
			DOHC		
	Bore Stroke(mm)		86.0 94.6		
	Displacement(cc)		2198		
	Compression ratio		10.0		
	Fuel system		Electrical Control Fuel Injection		
Fuel tank capacity(l)		58			
PERFORM- ANCE	Max output(DIN) kW(ps)/rpm		108(147)/5800		
	Max torque(DIN) N m(kg-m)/rpm		203(20.7)/4000		
	10 15 mode Fuel consumption (km/l)		10.0		
TRANSAXLE	Gear ratio	1st	3.672		
		2nd	2.098		
		3rd	1.391		
		4th	1.000		
		Rev.	4.022		
	Final reduction gear ratio		4.170		
CHASSIS	Steering		Rack and Pinion		
	Suspension	Front	McPherson strut type, Independent, Coil spring		
		Rear	Torsion beam type trailing-arm, Independent, Coil spring		
	Minimum turning circle<at tire> (m)		10.6	11.0	10.6
	Brakes	Front	Ventilated disc brakes		
		Rear	Disk brakes		
Tires		195/65R15	205/55R16	195/65R15	

*1 Roof rails attached 2 Sunroof attached